



## VI-MA-89D3b Vandal resistant Dome camera

A vandal resistant colour dome camera with auto switch to monochrome at low light level.



### Main features

- Colour camera with auto switch to monochrome at low light level
- Fixed camera/lens combination
- Signal 625 11/50Hz PAL standard

### Technical Specifications

Image Sensor	1/3" Sony CCD
Resolution	550TVL
Sensitivity (LUX)	0.001 (F1.2)
Electronic shutter	1/50-1/120,000
Lens	Varifocal auto IRIS lens 4-9mm / 2.8-11mm Direct Drive
BLCLow/ DNR	Middle/High/Off selectable Digital Noise Reduction

Gamma	0.45 (Adjustable range: 0.05 to 1),
Power	Local power 12-48VDC Remote power 24-48V AC/DC
Power consumption	1.2W
Video signal	Video connection for 2-wire twisted pair (up to 400m) or Coax Composite 1V P-P
Directional Adjustment	3 axis gimbal

### Mechanical specification

Dimension (mm)	Ø148x118
Net Weight (kg)	0.95
Mounting	Wall or ceiling
Use	Ceiling mount for outdoor use Ceiling and wall mount for indoor use

### Environmental specification

Operating temperature	-10 to 55°C
Humidity range	20 to 85% relative non-condensing.